



Contact our sales team to discuss your testing needs.  
 We look forward to working with you.  
 800-969-4050 • DATASYSTtest.com

**ENVIRONMENTAL CHAMBERS: HOT / COLD**

Chamber size	Capability	Quantity
32 <sup>3</sup>	-68C to 177C	1
27 <sup>3</sup>	-68C to +177C	2
16 <sup>3</sup>	-69C to +177C	1
8 <sup>3</sup>	-68C to +177C	1



**ENVIRONMENTAL CHAMBERS: HOT / COLD / HUMIDITY**

Chamber size	Capability	Quantity
27 <sup>3</sup>	-30C to 177C (humidity)	1
27 <sup>3</sup>	-15C to +93C (steady state humidity)	1
8 <sup>3</sup>	-68C to +177C (humidity)	1
8 <sup>3</sup>	-65C to +150C (humidity)	1

**ENVIRONMENTAL CHAMBER WITH VIBRATION CAPABILITY (AGREE CHAMBER)**

Chamber size	Capability	Quantity
32 <sup>3</sup>	-73C to +177C (AGREE Chamber)	1
32 <sup>3</sup>	-40C to +170C (AGREE Chamber)	1



**THERMAL SHOCK CHAMBERS**

Chamber size	Capability	Quantity
Two chamber 1-foot basket	-40C to +150C	1
Two Chamber 2-foot basket	-40C to +200C	1

**WALK-IN CHAMBERS**

Chamber size	Capability	Quantity
5' x 7' width door: 3' x 8'	-70C to +300C (humidity)	1
20' x 8.5' x 9.5'h Door 1: 59"x82" Door 2: 4' x 8'	-60C to +82C	1



**ALTITUDE CHAMBERS**

Chamber size	Capability	Quantity
~3 <sup>3</sup> feet; 18 x 22 x 13	22"Hg / -40C to +100C	1
Special Use; 68"wx52"dx88"t	Call for Details	1

Chamber rates are available upon request. Rates do not include set-up, monitoring and/ or functional testing that may be required for your test. Our team is able to provide a custom proposal for your testing requirements – call us today at 800-969-4050.